

# Microscale fluid handling system

**Publication number:** JP2002515820 (T)

**Publication date:** 2002-05-28

**Inventor(s):**

**Applicant(s):**

**Classification:**

- **International:** G01N27/62; B01J4/00; B01J19/00; B01L3/02; G01N30/72; G01N35/08; G01N37/00; H01J49/04; G01N30/46; G01N30/60; G01N30/62; G01N35/10; G01N27/62; B01J4/00; B01J19/00; B01L3/02; G01N30/00; G01N35/08; G01N37/00; H01J49/02; G01N35/10; (IPC1-7): B01J4/00; B01J19/00; G01N27/62; G01N35/08; G01N37/00

- **European:** H01J49/16E; B01J19/00R; B01L3/02D; B01L3/02D10; G01N30/72L2D

**Application number:** JP19970506906T 19960719

**Priority number(s):** US19950001349P 19950721; US19960675177 19960703; W/O1996US11985 19960719


**Also published as:**

US5872010 (A)  
CA2227331 (A1)  
CA2227331 (C)

Abstract not available for JP 2002515820 (T)

Abstract of corresponding document: US 5872010 (A)

A microscale fluid handling system that permits the efficient transfer of nanoliter to picoliter quantities of a fluid sample from the spatially concentrated environment of a microfabricated chip to "off-chip" analytical or collection devices for further off-chip sample manipulation and analysis is disclosed. The fluid handling system is fabricated in the form of one or more channels, in any suitable format, provided in a microchip body or substrate of silica, polymer or other suitable non-conductive material, or of stainless steel, noble metal, silicon or other suitable conductive or semi-conductive material. The microchip fluid handling system includes one or more exit ports integral with the end of one or more of the channels for consecutive or simultaneous off-chip analysis or collection of the sample. The exit port or ports may be configured, for example, as an electrospray interface for transfer of a fluid sample to a mass spectrometer.



Data supplied from the esp@cenet database — Worldwide